

Compact ANSI Switchboard Meter Amp, Volt and Frequency

The new Crompton Instruments compact ANSI switchboard meter offers Class 1 accuracy metering performance packed in a low profile, depth saving case. The 007 switchboard meters are a direct drop-in replacement for our legacy switchboard products.

The new compact case also offers a lightweight, heavy duty polycarbonate case which is electrically safe.

The 4½ inch meter complies with ANSI-C39.1 specifications.

Specifications

| Accuracy | Class 1 |
|------------------------------|----------------------------------|
| Specification | ANSI C39.1 |
| | |
| Scale length | 6.9" ~179mm |
| Scale | 250° |
| | |
| AC rms meters | 30% 3rd harmonic influence <1.5% |
| Temperature range | 32-140°F (0-60°C) |
| Temperature influence | 0.033% °F typical (0.06% °C) |
| Terminal studs | 10/32 UNF |
| Mounting studs | 1/4" UNF |
| Overloads | 1.2x continuous, AC current 20x |
| | for 1 second |
| Sealing | to IP 54 front of panel |
| Response time | approx 2.5 sec to FS |
| Calibrated for vertical pane | l mounting |

Dimensions 109.40 (4.31) (4.31) (5.52) UNI TERMANUS Panel Cut Out 85.60 (1.69) (1.69) (1.69)



holes. 31") DIA. FOR PANELS UP TO 8.00 (0.31") THICK 37") DIA. FOR PANELS OVER 8.00 (0.31") THICK



Product Coding System

| Model | Function |
|----------|---|
| 007-05FA | AC rms reading ammeter, linear scale, left zero |
| 007-05GA | AC rms reading voltmeter, linear scale, left zero |
| 007-05VA | DC voltmeter, left zero |
| 007-05AA | DC milliammeter/millivoltmeter, left zero |
| 007-05CA | DC milliammeter/millivoltmeter, centre zero |
| 007-05RA | DC milliammeter, suppressed zero (4/20mA etc) |
| 007-055A | DC transducer indicator, scaled watts |
| 007-056A | DC transducer indicator, scaled var |
| 007-41LA | AC frequency meter |

Product Code and Ordering Information Example

007-05GA-ZSUJ-C7

Accessories

The Compact ANSI Switchboard meter also comes with a range of accessories to compliment the product.

- Cable Clamp
- Terminal Cover

Features

Low profile Class 1 accuracy Optional panel gasket Reliability Long scale 240°

Benefits

Enhanced safety Reinforced insulation ANSI C39.1

Applications

Switchgear Distribution systems Energy management Process control Building management

Approvals

c-UL-us Listed E203000

Input Range Coding

(Popular codes only - other options available)

Ammeter Codes

| Code | Range |
|------|-------------|
| LA | 0-1A rms |
| LS | 0-5A rms |
| MT | 0-10A rms |
| EA | 0-200uA |
| FA | 0-1mA |
| HF | 0-20mA |
| EA | 100-0-100uA |
| FG | 1-0-1mA |
| HG | 4-20mA |
| | |

Voltmeter Codes

| Code | Range |
|------|-------------|
| PZ | 0-150V rms |
| RS | 0-250V rms |
| RX | 0-300V rms |
| SJ | 0-600V rms |
| Z4 | 0-10V DC |
| NL | 0-30V DC |
| PZ | 0-150V DC |
| RX | 0-300V DC |
| EY | 0-50mV/4mA |
| GB | 50-0-50mV |
| GM | 100-0-100mV |
| ZS | 142.86V rms |
| PZ | 150V rms |
| PS | 125V rms |

Scaling Meter Codes

| Code | Range |
|------|-------------|
| UJ | 5000V AC |
| RN | 200-250V AC |
| SE | 380-480V AC |
| SJ | 0-600V AC |
| SN | 0-800A AC |
| WC | 0-15KV AC |

| Code | Hz Range |
|------|----------|
| AN | 55-65Hz |
| AG | 45-55Hz |
| C6 | 60Hz |
| C7 | 50-60 Hz |

How to order

To order an equivalent for a 077 type meter, order exactly the same code, except replace 077 with 007.

E.g: 077-05FA-LSPK-C7 is 0-5A electrical scale, 0-100A dial AC ammeter, 50-60Hz. 007-05FA-LSPK-C7 provides identical specification in compact body style

While TE has made every reasonable effort to ensure the accuracy of the information in this catalog, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications. TE connectivity (logo) and TE Connectivity are trademarks of the TE Connectivity Ltd. family of companies. Crompton is a trademark of Crompton Parkinson and is used by TE Connectivity Ltd. under a licence. Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

TE Energy - innovative and economical solutions for the electrical power industry: cable accessories, connectors & fittings, insulators & insulation, surge arresters, switching equipment, street lighting, power measurement and control.

Tyco Electronics Corporation

8000 Purfoy Road Fuquay Varina, NC 27526-9349 Tel: 800.327.6996 Fax: 800.527.8350 E-mail: cromptonusa@tycoelectronics.com www.cromptonusa.com www.crompton-instruments.com

